
| | SITE PLAN NOTES | | | | | | | | |
|----|--|--|--|--|--|--|--|--|--|
| # | DESCRIPTION | | | | | | | | |
| 1 | THESE PLANS AND SPECIFICATIONS ARE THE PROPERTY OF: COLLINSON, OLIFF AND ASSOCIATES, INC. | | | | | | | | |
| 2 | IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO MEET ALL OF THE REQUIREMENTS OF THE FEDERAL, STATE, AND LOCAL AUTHORITIES, HEALTH DEPARTMENT AND UTILITY COMPANIES, IN ADDITION TO THE INFORMATION STATED ON THESE PLANS. | | | | | | | | |
| 3 | IN CASE OF CONFLICT BETWEEN ANY PART OF THESE PLANS AND SPECIFICATIONS, OR IF ANY ERRORS OR OMISSIONS ARE DISCOVERED IN THE LINES, GRADES AND DIMENSIONS, THE CONTRACTOR SHALL NOTIFY THE SITE CONSULTANT IMMEDIATELY AND SHALL REQUEST A WRITTEN DETERMINATION PRIOR TO PROCEEDING WITH THE WORK INVOLVED. IF THE WORK PROCEEDS WITH THE KNOWLEDGE OF THE ERROR OR OMISSION, AND WITHOUT A WRITTEN DETERMINATION, SUCH WORK WILL NOT BE CONSIDERED IN COMPLIANCE WITH THESE PLANS AND SPECIFICATIONS. | | | | | | | | |
| 4 | PRIOR TO CONSTRUCTION, CONTACT: THE ENFORCEMENT DIVISION, DEPARTMENT OF THE ENVIRONMENT SEDIMENT AND STORMWATER MANAGEMENT ADMINISTRATION 1800 WASHINGTON BLVD. BALTIMORE, MARYLAND 21230 PHONE: (410) 537-3000 | | | | | | | | |
| 5 | NOTIFY THE CALVERT COUNTY DEPARTMENT OF INSPECTIONS AND PERMITS, (410) 535-2155, THE CALVERT COUNTY SOIL CONSERVATION DISTRICT, (410) 535-1521, AND MISS UTILITY, (800) 257-7777, 3 DAYS PRIOR TO THE START OF ANY WORK ON THIS SITE. | | | | | | | | |
| 6 | OWNER(S): BD OF COMMISSIONERS OF CALVERT COUNTY CALVERT COUNTY TREASURER 175 MAIN ST PRINCE FREDERICK, MD 20678 PHONE: 410-326-4640 | | | | | | | | |
| 7 | DEVELOPER: KOENIG PRIVATE FOUNDATION STACEY HANN-RUFF 13480 DOWELL RD DOWELL, MD 20629 PHONE: 410-326-4640 | | | | | | | | |
| 8 | IT SHALL BE DISTINCTLY UNDERSTOOD THAT FAILURE TO MENTION SPECIFICALLY ANY WORK WHICH WOULD NATURALLY BE REQUIRED TO COMPLETE THIS PROJECT SHALL NOT RELIEVE THE CONTRACTOR OF HIS RESPONSIBILITY TO COMPLETE SUCH WORK. | | | | | | | | |
| 9 | AS CONSTRUCTION PROCEEDS, ADDITIONAL MEASURES MAY BE EMPLOYED WITH THE ENGINEER'S APPROVAL, IF CONDITIONS WARRANT, TO ENSURE EFFECTIVE STORMWATER DRAINAGE AND SEDIMENT CONTROL. | | | | | | | | |
| 10 | SEDIMENT CONTROL MEASURES AND PROPOSED TREE LINE REPRESENTS LIMIT OF WORK UNLESS OTHERWISE STATED. | | | | | | | | |
| 11 | ALL ELEVATIONS SHOWN HEREON ARE IN REFERENCE TO BENCH MARKS AND MUST BE FIELD VERIFIED BY THE GENERAL CONTRACTOR PRIOR TO CONSTRUCTION. | | | | | | | | |
| 12 | ALL EXTERIOR LIGHTING PROPOSED FOR THIS SITE SHALL BE PERMANENTLY INSTALLED AND MOUNTED IN ACCORDANCE WITH THE IESNA LIGHTING HANDBOOK & RECOMMENDED PRACTICES AS DESCRIBED IN THE C.C.Z.O. ARTICLE 6-6.01. FIXTURES SHALL MEET FULL CUTOFF CRITERIA. | | | | | | | | |
| 13 | EXISTING ELEVATIONS SHOWN HEREON ARE FROM A FIELD RUN SURVEY BY C.O.A., INC. DATED 7/2/18 AND SUPPLEMENTED WITH CALVERT COUNTY AERIAL TOPOGRAPHY REFERENCED TO N.A.V.D. 88. EXISTING UTILITIES SHOWN ARE TAKEN FROM FIELD INFORMATION AND THE BEST AVAILABLE PLANS OF THE EXISTING UTILITIES. | | | | | | | | |
| 14 | NO PROPERTY LINE SURVEY PERFORMED BY C.O.A., FOR THE PREPARATION OF THESE PLANS. THE BEARINGS SHOWN HEREON ARE REFERENCED TO N.A.D. 83. | | | | | | | | |
| 15 | THIS PLAN WAS PREPARED WITHOUT THE BENEFIT OF A TITLE REPORT. THIS PLAT IS NOT A BOUNDARY SURVEY AND DOES NOT MEET THE MINIMUM STANDARDS FOR A BOUNDARY SURVEY AS DEFINED BY COMAR REGULATION. | | | | | | | | |
| 16 | NO NON-TIDAL WETLANDS DELINEATION PERFORMED FOR THE PREPERATION OF THESES PLANS. A NON-TIDAL WETLAND WAIVER REQUEST WAS GRANTED. | | | | | | | | |
| 17 | NO FOREST STAND DELINEATION PERFORMED FOR THE PREPARATION OF THESE PLANS. THE PROJECT IS EXEMPT FROM FOREST CONSERVATION REQUIRMENTS PER SECTION 8-3.02.B OF THE CALVERT COUNTY ZONING ORDINANCE. | | | | | | | | |
| 18 | THERE ARE NOT ANY FLOOD PLAINS (FIRM PANEL #24009C0252G, DATED 11/19/14), THAT IMPACT THIS SITE WITHIN THE LIMIT OF DISTURBANCE. | | | | | | | | |

ANNMARIE GARDENS ~ SPR 2018 - 282

WILDFLOWER MEADOW & PATIO

TM 44 GRID 11 PARCEL 389 ~ 13480 DOWELL RD FIRST DISTRICT, CALVERT COUNTY DOWELL, MARYLAND 20629 FOR: KOENIG PRIVATE FOUNDATION



| ADJACENT PROPERTIES INFORMATION | | | | | | | | |
|---------------------------------|---------|--|----------------------|--|--|--|--|--|
| | PARCEL# | OWNER | DEED REFERENCE | | | | | |
| A | 566 | KOENIG PRIVATE FOUNDATION INC | K.P.S. 1331 / 471 | | | | | |
| B | 50 | SOLOMONS NURSING CENTER INC | A.B.E. 500 / 147 | | | | | |
| © | 40 | BRECKENRIDGE FAMILY TRUST | A.B.E. 4086 / 241 | | | | | |
| (D) | 490 | MENCIA JUAN M | A.B.E. 369 / 758 | | | | | |
| E | 695 | BD OF COMMISSIONERS CALVERT CO | 5120 / 190 | | | | | |
| F | 695 | LANCASTER JEANNE V | K.P.S. 4287 / 308 | | | | | |
| G | 696 | BD OF COMMISSIONERS CALVERT CO | K.P.S. 3490 / 163 | | | | | |
| H | 687 | KORTOKRAX ANTHONY EARL KORTOKRAX KATIE LYN | K.P.S. 4185 / 194 | | | | | |
| | 611 | LANGLEY JAMES F | K.P.S. 2027 / 182 | | | | | |
| <u>J</u> | 611 | HOMEOWNERS ASSOCIATION OF OSPREY COVE INC | K.P.S. 2111 / 740 | | | | | |
| K | 389 | BD OF COMMISSIONERS CALVERT CO | A.B.E. 597 / 434 | | | | | |
| (L) | 243 | KLA BAI COLEMAN-KLA JUDY | K.P.S. 4105 / 202 | | | | | |
| M | 385 | LANE TIM M & REECE LAURA J | K.P.S. 3700 / 01 | | | | | |
| N | 127 | HENDERSHOT ROBERT LUNDGREN KAREN | A.B.E. 5231 / 389 | | | | | |
| <u></u> | 126 | HUTCHINS CORA ELIZABETH TRUSTEES | K.P.S. 1371 / 690 | | | | | |
| P | 125 | 970 CURTIS RD DOWELL 20629-0000 | K.P.S. 1537 / 243 | | | | | |
| @ | 124 | HIGGINS THOMAS L WOODFIN FLOYD L | K.P.S. 4742 / 431 | | | | | |

| | SITI | E DATA E | BLOCK | , | | | L | LEGEND | | LIS | ST OF ABBREVIATIONS |
|--|--------|------------------------------|------------|--------------|--------------|-----------|------------------------------|--|---------------------------------------|--------|------------------------------|
| TAX MAP 44 GRID 11 | | 389 | DEED | 591 / 434 | TAX ID# | 01-015656 | DESCRIPTION | EXISTING | PROPOSED | ABBREV | DESCRIPTION |
| TAX MAP - GRID - PARCEL AREA | PARCEL | - | DEED 28.8 | - 39 AC ± | TAX ID# | - | BEOOK! HOW | | T NOT COLD | ASP-2 | ALUMINIZED STEEL PIPE-TYPE 2 |
| ZONING | | RESIDENTIAL | | | EV AREA (LDA | ۹) | BENCHMARK | (BM) A | | BRL | BUILDING RESTRICTION LINE |
| BUILDING RESTRICTION LINES: F PARKING RESTRICTION LINES: F | | 35 20 | SIDE | 35 20 | REAR REAR | 35 20 | BUILDING | | | BW | BOTTOM OF WALL |
| | | ISTING | SIDE | | N PROFIT PAR | | - CURB | | | CONC | CONCRETE |
| LAND USE | | POSED | | | N PROFIT PAR | RK | CURB | O DS#1 | ⊠ DS #1 | COTG | CLEANOUT TO GRADE |
| FLOOR AREA RATIO | | TING SF± OSED SF± | - | 18 | 8,146 0 | | DOWNSPOUT | " | | EL | ELEVATION |
| (INTERIOR INFO) | | TAL SF± | | 1: | 8,146 | | ELEVATION - CONTOUR | - <u>118</u> — — — — — — — — — — — — — — — — — — — | 118 | ELEC | ELECTRIC |
| | | A.R. | _ | | 0.02 | | ELEVATION - SPOT | 123X45 | 123.45 X | ES | END SECTION |
| UTILITIES | | ATER EWER | | | BLIC WATER | | FENCE - SCREENING | | | EX | EXISTING |
| | SC | OIL SYMBOL - S | • | , | HYDRIC | K VALUE | FEINCE - SCREENING | | | FFE | FINISHED FLOOR ELEVATION |
| PREDOMINANT SOILS | DeA | - DODON-CROS PcB - PICCOW | | | NO NO | 0.24 | FENCE - SECURITY | xx | xx | FH | FIRE HYDRANT |
| POWER | | FUD - FICCOV | | CTRIC | INU | 0.37 | FLOW ARROW | ^\- - | | FM | FORCE MAIN |
| WASTE | | | | N-SITE TRASH | | | GUARD RAIL | 000- | • • • | НВ | HORIZONTAL BEND |
| LAND COVERAGE (LOD) | | RVIOUS | GREEN 0.47 | FOREST | OTHER | TOTAL | | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | | НС | HANDICAP |
| PROPOSED SITE AC ± | | 0.07 0.20 | 0.47 | 0.00 | 0.00 | 0.54 | LIGHT - BUILDING MOUNTED | | | I | INLET |
| | | | | | | | LIGHT - PARKING LOT / STREET | | | L | LENGTH |
| | | | | | | | LIGHT - BOLLARD | \$ | • | LOD | LIMIT OF DISTURBANCE |
| | | | | | | | LIMIT OF DISTURBANCE | | —— LOD —— | МН | MANHOLE |
| | | | | | | | DAVEMENT CRAVE | 00000000000 | 00000000 | OAE | OR APPROVED EQUAL |
| | | | | | | | PAVEMENT - GRAVEL | | | PC | POINT OF CURVATURE |
| | | | | | | | PAVEMENT - SHA / COUNTY | 111111111111111111111111111111111111111 | | PRL | PARKING RESTRICTION LINE |
| | | | | | | | PAVEMENT - SITE | | | PT | POINT OF TANGENCY |
| | | | | | | | PIPE FOUND/IRON ROD FOUND | o PF / IRF | | PVC | POLYVINYL CHLORIDE |
| | | | | | | | | | | R | RADIUS |
| | | | | | | | PROPERTY LINE OR R/W LINE | | | R/W | RIGHT-OF-WAY |
| | | | | | | | RETAINING WALL | | | S | SANITARY SEWER |
| | | | | | | | SIDEWALK - BRICK | | | SHC | SEWER HOUSE CONNECTION |
| | | | | | | | SIDEWALK - CONCRETE | | | STA | STATION STATION |
| | | | | | | | | | <u> </u> | | |
| | | | | | | | SIGN | 0 3107 | • 🕠 | TBR | TO BE REMOVED |
| | | | | | | | 15% STEEP SLOPES | | | TC | TOP OF CURB |
| | | | | | | | 25% STEEP SLOPES | | | TRANS | TRANSFORMER |
| | | | | | | | SURGE STONE / RIP-RAP | | | TS&V | TAPPING SLEEVE & VALVE |
| | | | | | | | | | | TW | TOP OF WALL |
| | | | | | | | TO BE REMOVED | | | VHC | VAN HANDICAP |
| | | | | | | | TREE LINE | uuuuuu | · · · · · · · · · · · · · · · · · · · | W | WATERLINE |
| | | | | | | | UTILITY - GAS LINE | ——— EX G——— | ——— GAS ——— | WHC | WATER HOUSE CONNCECTION |
| | | | | | | | | —— OHW ——— | | WM | WATER METER |
| | | | | | | | UTILITY - OVER HEAD WIRES | | | WV | WATER VALVE |
| | | | | | | | UTILITY - POLE | | | YC | YELLOW CURB |
| | | | | | | | UTILITY - SEWER LINE | — EX 4in S — | S | | |
| | | | | | | | UTILITY - STORMDRAIN | | 15" HDPE | | |
| | | | | | | | UTILITY - STORMDRAIN INLET | | | | |
| | | | | | | | UTILITY - WATER LINE | — EX W — | w | | |
| | | | | | | | O HELL WALLEN EINE | | | | |

UTILITY - WELL

SURVEYOR'S / ENGINEER'S CERTIFICATE

I HEREBY CERTIFY THAT THIS PLAN OF EROSION AND SEDIMENT CONTROL MEETS THE REQUIREMENTS, STANDARDS AND SPECIFICATIONS OF

OWNER'S / DEVELOPER'S CERTIFICATE

AND/OR DEVELOPMENT WILL BE DONE PURSUANT TO THIS PLAN AND THAT ANY RESPONSIBLE PERSONNEL INVOLVED IN THE CONSTRUCTION PROJECT WILL HAVE A CERTIFICATE OF ATTENDANCE AT A MARYLAND DEPARTMENT OF THE SEDIMENT AND EROSION BEFORE BEGINNING THE PROJECT, I HEREBY AUTHORIZE THE RIGHT OF ENTRY FOR PERIODIC ON-SITE EVALUATION BY STATE OF MARYLAND, DEPARTMENT OF THE ENVIRONMENT, COMPLIANCE

DATE:1/16/19
FOR: KOENIG PRIVATE FOUNDATION

SITE DETAILS

| INDEX OF DRAWINGS | | | | | | | |
|--|---------------|----|------------|--|--|--|--|
| SHEET NAME | SHEET # | OF | TOTAL # | | | | |
| COVER SHEET | C 1.0 | OF | 11 | | | | |
| SPECIFICATIONS | C 1.1 | OF | 11 | | | | |
| PRE AND POST DEVELOPMENT DRAINAGE MAPS | C 1.2 - C 1.3 | OF | 11 | | | | |
| SEDIMENT & EROSION CONTROL AND DEMO PLAN | C 2.0 | OF | 11 | | | | |
| GRADING PLAN | C 3.0 | OF | 11 | | | | |
| STORMWATER MANAGEMENT PLAN & DETAILS | C 4.0 - C 4.1 | OF | 11 | | | | |
| SITE & LAYOUT PLAN | C 5.0 | OF | 11 | | | | |
| SEDIMENT & EROSION CONTROL AND STORM DRAIN | C 6 0 | OF | 11 | | | | |





DEPT. OF PUBLIC WORKS STATEMENT

DPW APPROVAL SIGNIFIES A FINDING OF COMPLIANCE TO THE CALVERT COUNTY ROAD AND STORMWATER MANAGEMENT ORDINANCES. REGARDLESS OF SUCH APPROVAL, THE DESIGN PROFESSIONAL, DEVELOPER, AND CONTRACTOR REMAIN SOLELY RESPONSIBLE FOR THE DESIGN AND FOR CORRECTING ANY AND ALL ERRORS, PROBLEMS, AND CODE VIOLATIONS PRIOR TO ANY ACCEPTANCE OF A FACILITY OR STRUCTURE BY THE COUNTY. THE APPROVAL OF DPW IS NOT A WAIVER OR RELEASE FOR DEFECTS OR DEVIATION IN DESIGN OR CONSTRUCTION.

AGENCY APPROVAL STAMPS

THIS STAMP IN RED COLOR INDICATES ORIGINAL

GP#: C 1.0 SPR#: 2018-282 PLAN#: 3 FILE #: B - 57 - 3

| nig\08 | | | | | | | | | |
|----------|--|--|------------------|-----------------|--|--|--|--|--|
| 12 Koe | BENCHMARK INFORMATION ~ NAD 83 & NAVD 88 | | | | | | | | |
| -128′ | BM# | DESCRIPTION | NORTH COORDINATE | EAST COORDINATE | | | | | |
| Series/1 | 1 | LETTER "F" OF "FRANCIS KOENIG" ON EDGE OF WATERMAIN | 247678.51 | 1469203.31 | | | | | |
| 2800 S | 2 | CENTER POINT OF CENTER CIRCLE OF COUNCIL RING | 247771.54 | 1469670.99 | | | | | |

30.93

30.42

2) EARTHWORK:

A) GENERAL

- 1. ALL TREES, STUMPS, RUBBISH, DEBRIS, ROOTMAT AND ORGANIC MATERIAL SHALL BE REMOVED FROM THE LIMITS OF THE GRADING.
- 2. FILLING MAY BE ACCOMPLISHED AFTER DEMOLITION, CLEARING AND GRUBBING IS COMPLETED AND UNSUITABLE SOILS HAVE BEEN REMOVED.
- 3. NO FILL IS TO BE PLACED ON FROZEN GROUND.
- 4. NO SLOPES ARE TO BE GREATER THAN 2:1 WITHOUT MECHANICAL STABILIZATION. 5. ALL FILL SLOPES SHALL BE STABILIZED IMMEDIATELY AFTER COMPLETION OF GRADING SAID
- 6. TOPSOIL SHALL BE REMOVED PRIOR TO PLACING ANY CONTROLLED FILLS. 7. ALL AREAS TO BE SEEDED AND MULCHED ARE TO RECEIVE A MINIMUM 4 INCHES OF
- B) SITE CONSTRUCTION STATED ON THESE PLANS SHALL BE IN ACCORDANCE WITH THE MARYLAND DEPARTMENT OF TRANSPORTATION, STATE HIGHWAY ADMINISTRATION STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, DATED 2008, AS AMENDED. THE CONSTRUCTION SHALL ALSO BE BE GOVERNED BY THE STATE OF MARYLAND DEPARTMENT OF THE ENVIRONMENT PERMITS, U.S. ARMY CORPS OF ENGINEER PERMITS, AND THE MARYLAND STATE HIGHWAY AND COUNTY ROAD, GRADING AND BUILDING PERMITS, WHERE APPLICABLE.

C) COMPACTION:

- 1) GENERAL: CONTROL SOIL COMPACTION DURING CONSTRUCTION PROVIDING MINIMUM PERCENTAGE OF DENSITY SPECIFIED FOR EACH AREA CLASSIFICATION INDICATED BELOW. IF COMPACTION AS INDICATED CANNOT BE ACHIEVED, REMOVE UNSUITABLE SOIL TO DEPTH REQUIRED, FILL AND COMPACT SOIL TO MEET REQUIREMENTS OR AS DIRECTED BY THE OWNERS REPRESENTATIVE
- 2) PERCENTAGE OF MAXIMUM DENSITY REQUIREMENTS: COMPACT SOIL TO NOT LESS THAN THE FOLLOWING PERCENTAGES OF MAXIMUM DENSITY FOR SOILS WHICH EXHIBIT A WELL-DEFINED MOISTURE RELATIONSHIP DETERMINED IN ACCORDANCE WITH ASTM D 698.
- a) AREAS OF PROPOSED CONCRETE SLAB AND PARKING SPACES: COMPACT TOP 12" OF EXISTING SUBGRADE AND EACH LAYER OF BACKFILL OR FILL MATERIAL AT 95%. COMPACT THE TOP 6" OF SUBGRADE AND BASE COURSE PAVEMENT MATERIAL TO AT LEAST 100%
- b) LAWN OR UNPAVED AREAS: COMPACT EACH LAYER OF BACKFILL OR FILL MATERIAL AT 90%.
- c) WALKWAYS: COMPACT EACH LAYER OF BACKFILL OR FILL MATERIAL AT 95% MAXIMUM DENSITY.
- d) BACKFILL: COMPACT EACH LAYER AT 95%.

3) MOISTURE CONTROL:

- a) WHERE SUBGRADE OR LAYER OF SOIL MATERIAL MUST BE MOISTURE CONDITIONED BEFORE COMPACTION, UNIFORMLY APPLY WATER TO SURFACE OF SUBGRADE, OR LAYER OF SOIL MATERIAL. APPLY WATER IN MANNER TO PREVENT FREE WATER APPEARING ON SURFACE DURING OR SUBSEQUENT TO COMPACTION OPERATIONS. 'MOISTURE CONTENT SHALL BE WITH- IN 3 PERCENT OF OPTIMUM MOISTURE CONTENT AS DETERMINED BY ASTM D 698.'
- b) IF SOILS ARE FOUND TO EXCEED THE OPTIMUM MOISTURE CONTENT RANGE OF -1 TO +4 PERCENT, THEN THE SOILS SHALL BE SCARIFIED TO BE BROUGHT INTO COMPLIANCE.

D) BACKFILL AND FILL:

-) USE SATISFACTORY ONSITE SOIL MATERIAL, APPROVED FOR USE BY THE OWNER OR THEIR REPRESENTATIVE.
- 2) GENERAL: PLACE ACCEPTABLE SOIL MATERIAL IN LAYERS TO REQUIRED SUBGRADE ELEVATIONS FOR EACH AREA CLASSIFICATION LISTED BELOW.
- a) UNDER EXCAVATIONS AND BACKFILL, USE SATISFACTORY EXCAVATED OR BORROW MATERIAL.
- b) UNDER GRASSED AREAS, USE SATISFACTORY EXCAVATED OR BORROW MATERIAL.
- c) UNDER WALKS, PARKING AREA, AND CONCRETE SLAB AREAS, USE SUBBASE MATERIAL, OR SATISFACTORY EXCAVATED OR BORROW MATERIAL, OR COMBINATION OF BOTH AS INDICATED ON THESE PLANS.
- d) UNDER PIPING AND CONDUIT, USE SUBBASE MATERIAL WHERE SUBBASE IS INDICATED UNDER PIPING OR CONDUIT: SHAPE TO FIT BOTTOM 90 DEGREES OF CYLINDER.
- 3) PLACEMENT AND COMPACTION: a) PLACE BACKFILL AND FILL MATERIALS IN LAYERS NOT MORE THAN 8" IN LOOSE DEPTH PER LAYER FOR MATERIAL COMPACTED BY HEAVY COMPACTION EQUIPMENT, AND NOT MORE THAN 4" IN LOOSE DEPTH FOR MATERIAL COMPACTED BY HAND- OPERATED TAMPERS.

E) GRADING:

- 1) GENERAL: UNIFORMLY GRADE AREAS WITHIN LIMITS OF GRADING. SMOOTH FINISHED SURFACES WITHIN SPECIFIED TOLERANCES, COMPACT WITH UNIFORM LEVELS OR SLOPES BETWEEN POINTS WHERE ELEVATIONS ARE INDICATED, OR BETWEEN SUCH POINTS AND EXISTING GRADES. GRADE SMOOTH AND EVEN, FREE OF VOIDS, COMPACTED AS SPECIFIED, AND TO REQUIRED ELEVATION. PROVIDE FINAL GRADES WITHIN A TOLERANCE OF 1/2", WITH POSITIVE DRAINAGE.
- 2) COMPACTION: AFTER GRADING, COMPACT SUBGRADE SURFACES TO THE DEPTH AND INDICATED PERCENTAGE OF MAXIMUM OR RELATIVE DENSITY FOR EACH AREA CLASSIFICATION.

F) PARKING SURFACE:

- 1) GENERAL: SUBBASE COURSE IS TO CONSIST OF PLACING SUBBASE MATERIAL IN LAYERS OF SPECIFIED THICKNESS, OVER SUBGRADE SURFACE TO SUPPORT A PAVEMENT BASE AND SURFACE COURSE.
- 2) GRADE CONTROL: DURING CONSTRUCTION, MAINTAIN LINES AND GRADES INCLUDING CROWN AND CROSS- SLOPE OF SUBBASE COURSE.
- 3) MATERIALS AND INSTALLATION: GRAVEL AND BITUMINOUS CONCRETE MATERIALS AND INSTALLATION ARE TO BE IN ACCORDANCE WITH THE MARYLAND DEPARTMENT OF TRANSPORTATION, STATE HIGHWAY ADMINISTRATION (SHA) STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, DATED 1993, AS AMENDED, AND INSTALLED AS SHOWN ON

G) FIELD QUALITY CONTROL:

1) QUALITY CONTROL TESTING DURING CONSTRUCTION: THE CONTRACTOR SHALL RETAIN A QUALIFIED THIRD PARTY TESTING SERVICE TO INSPECT AND CERTIFY THE SITEWORK CONSTRUCTION. CERTIFICATIONS SHALL INCLUDE SUBGRADE COMPACTION, FILL/BACKFILL MATERIAL AND COMPACTION, SUBBASE MATERIAL AND COMPACTION, AND CONCRETE MATERIALS.

SITE WORK SPECIFICATIONS (CONT.)

2) EARTHWORK: (CONT)

G) FIELD QUALITY CONTROL:

2) IF, IN THE OPINION OF THE OWNER OR OWNER'S REPRESENTATIVE, BASED ON TESTING, MATERIALS AND/ OR PLACEMENT OF MATERIALS ARE SUBSTANDARD, THE CONTRACTOR IS TO PROVIDE NEW MATERIALS, CONSTRUCTED AND TESTED, AT NO ADDITIONAL EXPENSE TO THE OWNER.

H) MAINTENANCE:

1) PROTECTION OF GRADED AREAS

- a) PROTECT NEWLY GRADED AREAS FROM TRAFFIC AND EROSION. KEEP FREE OF TRASH AND DEBRIS.
- b) REPAIR AND REESTABLISH GRADES IN SETTLED ERODED, AND RUTTED AREAS TO SPECIFIED TOLERANCES.

I) DISPOSAL OF EXCESS AND WASTE MATERIALS (IF REQUIRED):

1) REMOVE EXCESS EXCAVATED MATERIAL, TRASH, DEBRIS AND WASTE MATERIALS AND DISPOSE OF IT OFF OWNER'S PROPERTY IN A MANNER CONSISTENT WITH LOCAL. STATE AND FEDERAL AGENCIES.

J) DEWATERING:

1) THE CONTRACTOR SHALL PROVIDE ALL NECESSARY TEMPORARY DRAINAGE AND KEEP THE SAME OPERATING UNTIL PERMANENT DRAINAGE HAS BEEN COMPLETED. IF WATER IS ENCOUNTERED IN EXCAVATING AND UTILITY CONSTRUCTION, THE CONTRACTOR SHALL PROVIDE AND MAINTAIN PUMPS OF SUFFICIENT CAPACITY TO REMOVE THE WATER WHILE THE EXCAVATIONS ARE BEING MADE AND UNTIL THE CONCRETE FOOTINGS HAVE BEEN POURED THE FOUNDATION WALLS OR OTHER STRUCTURES ERECTED UP TO GRADE, AND THE EXCAVATION HAS BEEN BACKFILLED.

K) BRACING OR SHEETING:

1) THE CONTRACTOR SHALL SUPPORT THE SIDES AND ENDS OF ALL EXCAVATIONS WHEREVER NECESSARY OR DIRECTED WITH BRACES, SHEETING, SHORES OR STRINGS OF THE QUALITY AND CHARACTER REQUIRED TO PROVIDE ADEQUATE SUPPORT, AS GOVERNED BY LOCAL, STATE, AND FEDERAL REGULATIONS

3) SEEDING: PERMANENT AND TEMPORARY SEEDING:

- A) SEED PREPARATION: APPLY 100 POUNDS PER 1000 SQUARE FEET OF PULVERIZED LIMESTONE AND 12 POUNDS PER 1000 SQUARE FEET OF 10-20-20 EQUIVALENT FERTILIZER, HARROW OR DISC ON THE CONTOUR INTO THE SOIL TO A DEPTH OF 3 TO 4 INCHES, CONTINUE TILLAGE UNTIL A REASONABLY FINE SEEDBED HAS BEEN PREPARED.
- B) SEEDING: USE KENTUCKY 31, TALL FESCUE AT THE RATE OF 5 TO 7 POUNDS PER 1000 SQUARE FEET ON A MOIST SEEDBED, MINIMUM COVERAGE 1/4 INCH. STABILIZE BY MULCHING WITH UNWEATHERED, UNCHOPPED, SMALL GRAIN STRAW SPREAD AT THE RATE OF 1-1/2 TO 2 TONS PER ACRE. MULCH IS TO BE ANCHORED BY ASPHALT TIE- DOWN METHOD (OAE). SEEDING IS TO BE DONE ONLY BETWEEN FEBRUARY 1 AND APRIL 15 OR AUGUST 15 TO OCTOBER 15.
- C) TEMPORARY SEEDING TO BE DONE ON COMPLETION OF CONSTRUCTION SODDING: TO BE ROOTED KENTUCKY 31 TALL FESCUE. SOD SHALL BE TRANSPLANTED WITHIN 36 HOURS OF HARVESTING. EACH STRIP OF SOD TO BE PLANTED WITH AT LEAST 2 STAKES SPACED NOT MORE THAN 2 FEET APART.

D) VEGETATIVE STABILIZATION:

- ALL VEGETATIVE STABILIZATION PREPARATIONS, PROCEDURES, AND MATERIALS ARE TO BE IN COMPLIANCE WITH SECTION B GRADING AND STABILIZATION SUB-SECTION B-4 OF THE 2011 MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL MANUAL PREPARED BY THE MARYLAND DEPARTMENT OF THE ENVIRONMENT WATER MANAGEMENT ADMINISTRATION IN ASSOCIATION WITH THE NATURAL RESOURCES CONSERVATION SERVICE AND THE MARYLAND ASSOCIATION OF SOIL CONSERVATION DISTRICTS, AS AMENDED. FOLLOWING THE INITIAL DISTURBANCE OR RE-DISTRUBANCE, PERMANENT OR TEMPORARY STABILIZATION SHALL BE COMPLETED WITHIN:
- 1) THREE (3) CALENDAR DAYS AS TO THE SURFACE OF ALL PERIMETER CONTROLS (SUCH AS DIKES, SWALES, DITCHES), AND SLOPES STEEPER THAN 3H TO 1V (3:1) AND:

2) SEVEN (7) CALENDAR DAYS AS TO ALL OTHER DISTURBED AREAS ON THE PROJECT SITE.

E) THE REQUIREMENTS OF .08.05.01.06.(B)(E)(IV) DO NOT APPLY TO THOSE AREAS WHICH ARE SHOWN ON THE PLAN AND ARE CURRENTLY BEING USED FOR MATERIAL STORAGE, OR FOR THOSE OF A SURFACE MINE SITE, WHERE THE STABILIZATION MATERIAL WOULD CONTAMINATE THE RECOVERABLE RESOURCE. MAINTENANCE SHALL BE PERFORMED AS NECESSARY TO ENSURE THAT THE STABILIZED AREAS CONTINUOUSLY MEET THE APPROPRIATE REQUIREMENTS OF THE "STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL IN DEVELOPING AREAS" (2011), WHICH IS INCORPORATED BY REFERENCE IN REGULATION .08.05.01.10.

4) SEDIMENT AND EROSION CONTROL:

SEDIMENT AND EROSION CONTROL MEASURES ARE TO BE INSTALLED PER THE "MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL" MARYLAND DEPARTMENT OF THE ENVIRONMENT (2011) AS CURRENTLY AMENDED AND AS DETAILS STATED PER THESE PLANS.

5) FIRE PROTECTION:

- A) FIRE DEPARTMENT VEHICULAR ACCESS TO ALL STRUCTURES UNDER CONSTRUCTION SHALL BE PROVIDED AT ALL TIMES. IN AREAS WHERE GROUND SURFACES ARE SOFT OR LIKELY TO BECOME SOFT, HARD ALL-WEATHER SURFACE ACCESS ROADS SHALL BE PROVIDED.
- B) TRASH AND DEBRIS SHALL BE REMOVED FROM THE CONSTRUCTION SITE AS OFTEN AS NECESSARY TO MAINTAIN A FIRE-SAFE CONSTRUCTION SITE.
- C) AS-BUILT DRAWINGS SHOWING BUILDING FLOOR PLANS, FIRE PROTECTION SYSTEMS, AND ITEMS OF FIRE SUPPRESSION INTEREST SUCH AS STANDPIPE CONNECTIONS, SPRINKLER CONNECTIONS, HYDRANTS, ETC. SHALL BE SUBMITTED TO THIS OFFICE PRIOR TO ISSUANCE OF USE AND OCCUPANCY PERMIT UPON COMPLETION OF THE PROJECT.
- D) FIRE SUPPRESSION TANK (IF REQUIRED) TO BE FILLED WITH WATER PRIOR TO USE AND OCCUPANCY.

6) SOIL TESTS:

NO SITE SOIL BORINGS FOR EARTHWORK OPERATIONS PERFORMED FOR THE PREPARATION OF

7) WATER & SEWER / WELL & SEPTIC SYSTEM:

PUBLIC WATER & SEWER AND/OR PRIVATE WELL & SEPTIC SYSTEMS ARE TO BE CONSTRUCTED OR UTILIZED IN ACCORDANCE WITH ALL COUNTY AND STATE SPECIFICATIONS AND PERMITS.

SITE WORK SPECIFICATIONS (CONT.)

8) SIGNAGE

- A) ALL SITE SIGNAGE IS TO BE IN ACCORDANCE WITH THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES" DATED 1988 OR AS CURRENTLY AMENDED.
- B) ALL HANDICAP SPACES AND SIGNAGE ARE TO BE IN ACCORDANCE WITH THE AMERICAN DISABILITIES ACT (ADA) STANDARDS AS ADOPTED BY CALVERT COUNTY DATED SEPTEMBER 6,

9) BOUNDARY INFORMATION

- A) THIS PLAT IS A SPECIAL PURPOSE SURVEY PER SECTION 09.13.06.10 OF COMAR REGULATIONS.
- B) THE PROPERTY LINES SHOWN HEREON ARE BASED ON FIELD WORK PERFORMED BY C.O.A., INC.
- C) THIS PLAT IS NOT A BOUNDARY SURVEY AND DOES NOT MEET THE MINIMUM STANDARDS FOR A BOUNDARY SURVEY AS DEFINED BY COMAR REGULATION.

10) STORMWATER MANAGEMENT:

THE CONSTRUCTION OF THE STORMWATER MANAGEMENT SYSTEM(S) SYSTEM(S) IS TO BE IN ACCORDANCE WITH THE CALVERT COUNTY STORMWATER MANAGEMENT ORDINANCE, MAY 4, 2010 WHICH INCORPORATES BY REFERENCE THE MARYLAND DEPT. OF THE ENVIRONMENT "2000 MARYLAND STORMWATER DESIGN MANUAL, VOLUMES I & II AND THE USDA NATURAL RESOURCES CONSERVATION SERVICE CONSERVATION PRACTICE STANDARD POND CODE 378 ALL AS CURRENTLY AMENDED."

11) ARCHAEOLOGICAL AND HISTORICAL RESOURCES:

CONTRACTORS WORKING ON THIS PROJECT ARE HEREBY INFORMED THAT THERE IS A POSSIBILITY THAT ARCHAEOLOGICAL ARTIFACTS WILL BE ACCIDENTALLY DISCOVERED DURING ANY GROUND-DISTURBING ACTIVITIES, INCLUDING GRADING AND EXCAVATION. ARTIFACTS COULD INCLUDE STONE TOOLS (ARROWHEADS, FOR EXAMPLE), POTTERY, METALS, BRICKS, GLASS, BONE, ETC. IF ARTIFACTS ARE DISCOVERED. THE CONTRACTOR OR APPLICANT MUST CEASE WORK AND CONTACT THE DEPARTMENT OF PLANNING & ZONING, HISTORIC PRESERVATION PLANNER AT 410-535-2348 FOR PROMPT EVALUATION OF THE OBJECTS AND TO AVOID DELAYS TO THE PROJECT BY LAW, ALL ARTIFACTS BELONG TO THE PROPERTY OWNER, UNLESS THEY ARE HUMAN REMAINS WHICH CANNOT BE DISTURBED WITHOUT WRITTEN AUTHORIZATION FROM THE STATES ATTORNEY EVALUATION IN THE INTEREST OF DOCUMENTING THE HERITAGE AND UNDERSTAND THE PAST OF CALVERT COUNTY.

12) ENVIRONMENTAL FEATURES: (IF SHOWN ON PLANS)

- A) THE ISSUANCE OF COUNTY PERMITS OR APPROVALS IS A LOCAL PROCESS AND DOES NOT IMPLY THAT THE APPLICANT HAS MET STATE AND FEDERAL REQUIREMENTS FOR WETLANDS UNDER COMAR;THE FEDERAL WATER POLLUTION CONTROL ACT; OR THE RIVERS AND HARBORS ACT.
- B) A BUFFER ZONE OF 50-FOOT ADJACENT TO NON-TIDAL WETLANDS AND A 100-FOOT ADJACENT TO TIDAL WETLANDS SHALL BE MAINTAINED AND THE FOLLOWING ADDITIONAL REQUIREMENTS
- C) ANY BUFFER AREAS SHOWN ON THESE PLANS ARE TO BE LEFT UNDISTURBED IN PERPETUITY AND TO SERVE FOR WATER QUALITY BENEFITS.
- D) PROTECTIVE SNOW FENCING SHALL BE INSTALLED ALONG THE 50 FT WETLAND BUFFER WITHIN 100-FT OF THE LIMITS OF DISTURBANCE AND INSPECTED PRIOR TO ISSUANCE OF ANY BUILDING OR GRADING PERMITS FOR THE PROJECT.

E) A 10-FOOT SETBACK SHALL BE MAINTAINED FROM THE EDGE OF THE WETLAND BUFFER.

- F) FOREST RETENTION AREAS (FRA'S) ARE TO BE LEFT UNDISTURBED UNLESS APPROPRIATE APPROVALS OR PERMITS HAVE BEEN OBTAINED FOR THE REMOVAL OF TREES AND/OR UNDER STORY VEGETATION. TIMBER HARVESTS MAY OCCUR WITHIN (FRA'S) WITH AN APPROVED FORESTS HARVEST PLAN AND OTHER APPROPRIATE APPROVALS AND/OR PERMITS. OTHER THAN TIMBER HARVESTS, PERMITS MAY ONLY BE ISSUED FOR THE REMOVAL OF TREES OR UNDER STORY VEGETATION IF THEY ARE A THREAT TO STRUCTURES OR TO PROHIBIT THE SPREAD OF PLANT DISEASES. PERMITS MAY ALSO BE ISSUED FOR THE REMOVAL OF UNDER STORY PLANTS COMPOSED OF INVASIVE OR NOXIOUS PLANTS OR WEEDS. OTHERWISE, NO EQUIPMENT, MACHINERY, MOTOR VEHICLES, MATERIALS, STOCKPILING, DUMPING OF TRASH OR STRUCTURES ARE ALLOWED WITHIN THE FOREST RETENTION AREA. HIKING, NATURE OBSERVATION AND STUDY, AND WILDLIFE MANAGEMENT ACTIVITIES MAY OCCUR IN THE FOREST RETENTION AREAS.
- G) FOREST PROTECTION MEASURES ARE TO BE IN PLACE AND INSPECTED ON EACH LOT PRIOR TO ISSUANCE OF ANY BUILDING OR GRADING PERMITS FOR EACH LOT. STAKING, FLAGGING. FENCING AND POSTING SIGNS SHALL MARK THE BOUNDARY OF THE (FRA). ALL PROTECTIVE MEASURES SHALL BE MAINTAINED THROUGHOUT THE PROJECT.

13) STATE HIGHWAY ADMINISTRATION (S.H.A.) NOTE: (IF REQUIRED)

ALL CONSTRUCTION WITHIN THE PUBLIC S.H.A. RIGHT-OF-WAY (IF REQUIRED) SHALL BE IN ACCORDANCE WITH THE S.H.A. ENGINEERING ACCESS AND UTILITY PERMITS TO BE ISSUED FOR THIS SITE.

14) CALVERT COUNTY DEPARTMENT OF PUBLIC WORKS (DPW) NOTE: (IF REQUIRED)

ALL CONSTRUCTION WITHIN THE PUBLIC COUNTY RIGHT-OF-WAY (IF REQUIRED) SHALL BE IN ACCORDANCE WITH THE COUNTY ACCESS AND UTILITY PERMITS TO BE ISSUED FOR THIS SITE.

15) SITE PLAN NOTES

A) ALL EXISTING FEATURES ARE TO REMAIN UNLESS NOTED OTHERWISE.

- B) EXISTING PAVED SURFACES WHICH ARE PROPOSED TO BE LANDSCAPED GREEN AREAS SHALL HAVE ALL PAVEMENT, GRAVEL SUB GRADE MATERIAL REMOVED AND REPLACED WITH TOPSOIL TO THE EXTENT REQUIRED TO PROVIDE SUITABLE SOILS FOR THE ESTABLISHMENT OF LANDSCAPE MATERIALS.
- C) IN LOCATIONS WHERE PROPOSED PAVEMENT IS TO MEET EXISTING PAVEMENT, THE EXISTING PAVEMENT SHALL BE SAW CUT TO PROVIDE A NEAT AND CLEAN EDGE TO CONSTRUCT THE IMPROVEMENTS SHOWN HEREON.
- D) SEE ARCHITECTURAL PLANS FOR INFORMATION RELATED TO BUILDING, FOUNDATION AND UTILITY COORDINATION.


282 ∞ 2018 NTIO


> GARDE FLOWER 11 PARCE ANNMARIE (
> WILDFI
> TM 44 GRID 11
> FIRST DI
> DOV

THIS STAMP IN RED COLOR INDICATES ORIGINAL


C 1.1


FILE #: B - 57 - 3 A.1






X:\1-12800 Series\1-12812 Koenig\05-Drawing Files\C-site NEM









MICRO - BIORETENTION #1


SCALE: 1"=10'





LANDSCAPE PLAN

| MICRO-BIORETENTION LANDSCAPE SCHEDULE | | | | | | | | | |
|---------------------------------------|-----|----------------------|--------------------------------------|---------------------|---------------------------|--------------|--|--|--|
| SYMBOL | KEY | # | BOTANICAL NAME | COMMON NAME | SIZE, ROOT PREPARATION | SPACING | | | |
| TREES (SELECT AMONG SPECIES BELOW) | | | | | | | | | |
| | | | Chionanthus virginicus | White Fringetree | 1"-1.5" Cal. B&B | AS SHOWN | | | |
| | A | 1/300 SF | Amelanchier arborea | Downy Service-Berry | 1"-1.5" Cal. B&B | AS SHOWN | | | |
| | ^ | TOTAL 2 | Carpinus caroliniana | American Hornbeam | 1"-1.5" Cal. B&B | AS SHOWN | | | |
| | | _ | Crataegus crus-galli Cockspur Hawtho | | 1"-1.5" Cal. B&B | AS SHOWN | | | |
| | • | S | HRUBS (SELECT AM | ONG SPECIES BEL | OW) | | | | |
| | | 3/300 SF TOTAL | Rhododendron | Azalea | 3 GAL CONT | 3' OC / A.S. | | | |
| | | | Vaccinium corymbosum | Highbush Blueberry | 3 GAL CONT | 3' OC / A.S. | | | |
| * | В | | g. | | 18"-24" CONT | 3' OC / A.S. | | | |
| • | | 6 | Cephalanthus occidentalis | Buttonbush | 18"-24" CONT | 3' OC / A.S. | | | |
| | | GRO | JND COVER (SELEC | T AMONG SPECIES | BELOW) | | | | |
| | | 1/10 | Panicum virgatum | Switchgrass | 1 GAL CONT | 2' OC / A.S. | | | |
| | С | SE. | Lobella cardinalus | Cardinal flower | 1 GAL CONT | 2' OC / A.S. | | | |
| | | 51 | Iris brevicaulis | Lamance Iris | 1 GAL CONT | 2' OC / A.S. | | | |



| NTS | | | | | | | | | |
|---------------------------------|-----------|-----------|-----------|-----------|-----------|----------------|--------------------|--------------|--|
| MICRO-BIORETENTION DESIGN TABLE | | | | | | | | | |
| DIMENSION | | | | | | | | | |
| SYSTEM | A (FT) | B (FT) | C (FT) | D (FT) | L (FT) | SURFACE EL. | TOP OF BERM EL. | COMMENTS | |
| MB #1 | 2.0 | 1.0 | 10± | 0.33 | 50± | 27.75 | 28.5 | 500 SF (MIN) | |
| _ | - | _ | 1 | - | - | - | - | - | |

MICRO-BIORETENTION CONSTRUCTION, INSPECTION, AND MAINTENANCE CRITERIA:

Construction Criteria:

The following items should be addressed during construction of projects with micro-bioretention:

 Erosion and Sediment Control: Micro-bioretention practices should not be constructed until the contributing drainage area is stabilized. If this is impractical, runoff from disturbed areas shall be diverted away and no sediment control practices shall be used near the proposed location.

 Soil Compaction: Excavation should be conducted in dry conditions with equipment located outside of the practice to minimize bottom and sidewall compaction. Only lightweight, low ground-contact equipment should be used within micro-bioretention practices and the bottom scarified before installing underdrains and filtering media.

• Underdrain Installation: Gravel for the underdrain system should be clean, washed, and free of fines. Underdrain pipes should be checked to ensure that both the material and perforations meet specifications. The upstream ends of the underdrain pipe should be capped prior to installation.

• Filter Media Installation: Bioretention soils may be missed on-site before placement. However, soils should not be placed under saturated conditions. The filter media should be placed and graded using excavators or backhoes operating adjacent to the practice and be place in horizontal layers (12 inches per lift maximum). Property compaction of the media will occur naturally. Spraying or sprinkling water on each lift until saturated may quicken settling times.

• Landscape Installation: The optimum planting time is during the Fall. Spring planting is also acceptable but may require watering.

Inspection:

• Regular inspections shall be made during the following stages of construction:

During excavation to subgrade and placement and backfill of underdrain systems. During placement of filter media.

During construction of appurtenant conveyance.

Upon completion of final grading and establishment of permanent stabilization.

AsBuilt: Once construction is complete, the contractor shall provide an "As-Built" plan certification prepared by either a Professional Engineer or Professional Land Surveyor licensed in the State of Maryland to ensure that the ESD Planning Techniques, Treatment Practices, and Structural Stormwater Management measures and conveyance systems comply with the specification contained in the approved plans. At a minimum, "As-Built" certification shall include a set of drawings comparing the approved Stormwater Management Plan with what was constructed. The "As-Built" plan shall along with material certifications and inspection reports shall be submitted to the Engineer and Calvert County Department of Public Works for approval.

Maintenance Criteria:

The following items should be addressed to ensure proper maintenance and long-term performance of micro-bioretention practices:

• Privately owned practices shall have a maintenance plan and shall be protected by easement, deed restriction, ordinance, or other legal measures preventing its neglect, adverse alteration, and removal.

 The top few inches of filter media should be removed and replaced when water ponds for more than 48 hours. Silts and sediment should be removed from the surface of the filter bed when accumulation exceeds one

• Where practices are used to treat areas with higher concentrations of heavy metals (e.g., parking lots, roads), mulch should be replaced annually. Otherwise, the top two to three inches should be replaced as necessary.

 Occasional pruning and replacement of dead vegetation is necessary. If specific plants are not surviving, more appropriate species should be used. Watering may be required during prolonged dry periods.

AS-BUILT CERTIFICATION

I HEREBY CERTIFY THAT THE STORMWATER MANAGEMENT FACILITIES (BOTH BMPS AND ESD PRACTICES) SHOWN ON THE PLANS HAVE BEEN CONSTRUCTED IN ACCORDANCE WITH THE PLANS APPROVED BY THE CALVERT COUNTY DEPARTMENT OF PUBLIC WORKS., EXCEPT AS NOTED IN RED ON THE "AS-BUILT" DRAWINGS.

JOSEPH J. KADJESKI MD PE #31181


THIS STAMP IN RED COLOR INDICATES ORIGINAL C 4.0


ANNMARIE (


282

2018

FILE #: B - 57 - 3 D.1








RAINWATER HARVESTING MAINTANANCE, CONSTRUCTION & INSPECTION


SPRING / SUMMER


- Clear gutters at least once a year and cistern filter / screen as needed of leaf material, sticks, and other debris to prevent clogging and to prevent growth of bacteria.
- The water collected in your cistern should be used or drained completely at least every seven days. Mosquitos breed in standing water.
- If your cistern is in direct sunlight, algae may grow in the water. If it happens, drain the cistern and wash well with a weak bleach solution ($\frac{3}{4}$ cups of bleach for each gallon if water). Rinse the cistern afterward.
- Do not drink the water from a cistern.

Fall / Winter

- Cistern should be disconnected, drained, and cleaned before the start of the cold season to avoid damage from freezing.
- Remember to reconnect you rain spout when your cistern is not in use to divert water away from the structure.







TIMBER WIER DETAIL

| SYSTEM | SURFACE ELEV. (A) | TOP OF BERM ELEV. (B) | PONDING / TOP OF WEIR ELEV. (C) | PONDING DEPTH (D) | WEIR WIDTH (W) (FT) | TOTAL LENGTH (L) (FT) | OUTFALL LENGTH (FT) |
|--------|----------------------|--------------------------|---------------------------------------|----------------------|------------------------|--------------------------|------------------------|
| MB #1 | 27.75 | 28.5 | 28.08 | 0.23 | 8.0 | 17 | 6 |
| - | - | - | - | - | - | - | - |

| | ., | ABLE B.4.1 MATERIALS | |
|---|--|---|--|
| MATERIAL | SPECIFICATIONS | SIZE | NOTES |
| PLANTINGS | SEE APPENDIX A, TABLE A.4 | N/A | PLANTINGS ARE SITE-SPECIFIC |
| PLANTING SOIL (2' TO 4' DEEP) | LOAMY SANDS (60-65%) & COMPOST (35-40%) OR SANDY LOAM (30%), COARSE SAND (30%) & COMPOST (40%) | N/A | USDA SOIL TYPES OR SANDY LOAM; CLAY CONTENT LESS THAN 5% |
| ORGANIC CONTENT | MIN. 10% BY DRY WEIGHT (ASTM D 2974) | | |
| MULCH | SHREDDED HARDWOOD | | AGED 6 MONTHS, MINIMUM: NO PINE OR WOOD CHIPS |
| PEA GRAVEL DIAPHRAGM | PEA GRAVEL: ASTM-D-448 | NO. 8 OR NO. 9 (1/8" TO 3/8") | |
| CURTAIN DRAIN | ORNAMENTAL STONE : WASHED COBBLES | STONE 2" TO 5" | |
| GEOTEXTILE | | N/A | PE TYPE 1 NONWOVEN |
| GRAVEL (UNDERDRAINS AND INFILTRATION BERMS) | AASHTO M-43 | No. 57 OR No. 6 AGGREGATE (3/8" TO 3/4") | |
| JNDERDRAIN PIPING | F 758, TYPE PS 28 OR AASHTO M-278 | 4" TO 6" RIGID SCH 40 PVC | SLOTTED OR PERFORATED PIPE: 3/8" PERF. @ 6" ON CENTER, 4 HOLES PER ROW: MINIMUM OF 3" OF GRAVEL OVER AND BELOW PIPES: PERFORATED PIPE SHALL BE WRAPPED WITH 1/4" GALVINIZED HARDWAF CLOTH |
| POURED IN PLACE CONCRETE (IF REQUIRED) | MASH MIX NO. 3 PSI @ 28 DAYS, NORMAL WEIGHT, AIR-ENTRAINED; REINFORCING TO MEET ASTM-615-60 | N/A | ON SITE TESTING OF POURED-IN-PLACE CONCRETE REQUIRED: 28 DAY STREGTH AND SUMP TEST; ALL CONCRETE DESIGN (CAST-IN-PLACE OR PRE-CAST) NOT USING PREVIOUSLY APPROVED STATE OR LOCA STANDARDS REQUIRES DESIGN DRAWING SEALED AND APPROVED BY A PROFFESIONAL STRUCTUAL ENGINEER LICENSED IN THE STATE OF MARYLAND |
| SAND | AASHTO-M-6 OR ASTM-C-33 | 0.02" TO 0.04" | SAND SUBSTITUTIONS SUCH AS DIABASE AND GREYSTONE (AASHTO) #10 ARE NOT ACCEPTABLE. NO CALCIOM CARBONATE OR DOLOMITIC SAND SUBSTITUTIONS ARE ACCEPTABLE. NO "ROCK DUST" CAN BE USED FOR SAND. |

B.4.C SPECIFICATIONS FOR MICRO-BIORETENTION. RAIN GARDENS, LANDSCAPE INFILTRATION &

INFILTRATION BERMS

THE ALLOWABLE MATERIALS TO BE USED IN THESE PRACTICES ARE DETAILED IN TABLE B.4.1.

2. FILTERING MEDIA OR PLANTING SOIL

1. MATERIAL SPECIFICATIONS

THE SOIL SHALL BE A UNIFORM MIX. FREE OF STONES, STUMPS, ROOTS OR OTHER SIMILAR OBJECTS LARGEI THAN TWO INCHES. NO OTHER MATERIALS OR SUBSTANCES SHALL BE MIXED OR DUMPED WITHIN THE MICRO-BIORETENTION PRACTICE THAT MAY BE HARMEUL TO PLANT GROWTH, OR PROVE A HINDRANCE TO THE PLANTING OR MAINTENANCE OPERATIONS. THE PLANTING SOIL SHALL BE FREE OF BERMUDA GRASS. QUACKGRASS, JOHNSON GRASS, OR OTHER NOXIOUS WEEDS AS SPECIFIED UNDER COMAR 15.08.01.05.

THE PLANTING SOIL SHALL BE TESTED AND SHALL MEET THE FOLLOWING CRITERIA:

- SOIL COMPONENT LOAMY SAND OR SANDY LOAM (USDA SOIL TEXTURAL CLASSIFICATION) ORGANIC CONTENT - MINIMUM 10% BY DRY WEIGHT (ASTM D2974). IN GENERAL, THIS CAN BE MET WITH A MIXTURE OF LOAMY SAND (60% - 65%) AND COMPOST (35% TO 40%) OR SANDY LOAM (30%), COARSE SAND (30%), AND COMPOST (40%).
- CLAY CONTENT MEDIA SHALL HAVE A CLAY CONTENT OF LESS THAN 5%. • PH RANGE - SHOULD BE BETWEEN 5.5 - 7.0. AMENDMENTS (E.G., LIME, IRON SULFATE PLUS SULFUR) MAY BE MIXED INTO THE SOIL TO INCREASE OR DECREASE PH.

THERE SHALL BE AT LEAST ONE SOIL TEST PER PROJECT. EACH TEST SHALL CONSIST OF BOTH THE STANDARD SOIL TEST FOR PH, AND ADDITIONAL TESTS OF ORGANIC MATTER, AND SOLUBLE SALTS. A TEXTURAL ANALYSIS IS REQUIRED FROM THE SITE STOCKPILED TOPSOIL. IF TOPSOIL IS IMPORTED, THEN A TEXTURE ANALYSIS SHALL BE PERFORMED FOR EACH LOCATION WHERE THE TOPSOIL WAS EXCAVATED.

3. COMPACTION

IT IS VERY IMPORTANT TO MINIMIZE COMPACTION OF BOTH THE BASE OF BIORETENTION PRACTICES AND THE REQUIRED BACKFILL. WHEN POSSIBLE, USE EXCAVATION HOES TO REMOVE ORIGINAL SOIL. IF PRACTICES ARE EXCAVATED USING A LOADER, THE CONTRACTOR SHOULD USE WIDE TRACK OR MARSH TRACK EQUIPMENT, OR LIGHT EQUIPMENT WITH TURF TYPE TIRES. USE OF EQUIPMENT WITH NARROW TRACKS OR NARROW TIRES, RUBBER TIRES WITH LARGE LUGS, OR HIGH-PRESSURE TIRES WILL CAUSE EXCESSIVE COMPACTION RESULTING IN REDUCED INFILTRATION RATES AND IS NOT ACCEPTABLE. COMPACTION WILL SIGNIFICANTLY CONTRIBUTE TO DESIGN FAILURE

COMPACTION CAN BE ALLEVIATED AT THE BASE OF THE BIORETENTION FACILITY BY USING A PRIMARY TILLING OPERATION SLICH AS A CHISELPLOW RIPPER OR SLIBSOILER. THESE TILLING OPERATIONS ARE TO REFRACTURE THE SOIL PROFILE THROUGH THE 12 INCH COMPACTION ZONE. SUBSTITUTE METHODS MUST BE APPROVED BY THE ENGINEER. ROTOTILLERS TYPICALLY DO NOT TILL DEEP ENOUGH TO REDUCE THE EFFECTS OF COMPACTION FROM HEAVY EQUIPMENT.

ROTOTILL 2 TO 3 INCHES OF SAND INTO THE BASE OF THE BIORETENTION FACILITY BEFORE BACKFILLING THE OPTIONAL SAND LAYER. PUMP ANY PONDED WATER BEFORE PREPARING (ROTOTILLING) BASE.

WHEN BACKFILLING THE TOPSOIL OVER THE SAND LAYER, FIRST PLACE 3 TO 4 INCHES OF TOPSOIL OVER THE SAND, THEN ROTOTILL THE SAND/TOPSOIL TO CREATE A GRADATION ZONE. BACKFILL THE REMAINDER OF THE TOPSOIL TO FINAL GRADE

WHEN BACKFILLING THE BIORETENTION FACILITY, PLACE SOIL IN LIFTS 12" TO 18". DO NOT USE HEAVY EQUIPMENT WITHIN THE BIORETENTION BASIN. HEAVY EQUIPMENT CAN BE USED AROUND THE PERIMETER OF THE BASIN TO SUPPLY SOILS AND SAND. GRADE BIORETENTION MATERIALS WITH LIGHT EQUIPMENT SUCH AS A COMPACT LOADER OR A DOZER/LOADER WITH MARSH TRACKS.

4. PLANT MATERIAL

RECOMMENDED PLANT MATERIAL FOR MICRO-BIORETENTION PRACTICES CAN BE FOUND IN APPENDIX A,

5. PLANT INSTALLATION

COMPOST IS A BETTER ORGANIC MATERIAL SOURCE. IS LESS LIKELY TO FLOAT. AND SHOULD BE PLACED IN THE INVERT AND OTHER LOW AREAS. MULCH SHOULD BE PLACED IN SURROUNDING TO A UNIFORM THICKNESS OF 2" TO 3". SHREDDED OR CHIPPED HARDWOOD MULCH IS THE ONLY ACCEPTED MULCH. PINE MULCH AND WOOD CHIPS WILL FLOAT AND MOVE TO THE PERIMETER OF THE BIORETENTION AREA DURING A STORM EVENT AND ARE NOT ACCEPTABLE. SHREDDED MULCH MUST BE WELL AGED (6 TO 12 MONTHS)

ROOTSTOCK OF THE PLANT MATERIAL SHALL BE KEPT MOIST DURING TRANSPORT AND ON-SITE STORAGE. THE PLANT ROOT BALL SHOULD BE PLANTED SO 1/8TH OF THE BALL IS ABOVE FINAL GRADE SURFACE. THE DIAMETER OF THE PLANTING PIT SHALL BE AT LEAST SIX INCHES LARGER THAN THE DIAMETER OF THE PLANTING BALL. SET AND MAINTAIN THE PLANT STRAIGHT DURING THE ENTIRE PLANTING PROCESS. THOROUGHLY WATER GROUND BED COVER AFTER INSTALLATION.

TREES SHALL BE BRACED USING 2" BY 2" STAKES ONLY AS NECESSARY AND FOR THE FIRST GROWING SEASON ONLY. STAKES ARE TO BE EQUALLY SPACED ON THE OUTSIDE OF THE TREE BALL.

GRASSES AND LEGUME SEED SHOULD BE DRILLED INTO THE SOIL TO A DEPTH OF AT LEAST ONE INCH. GRASS AND LEGUME PLUGS SHALL BE PLANTED FOLLOWING THE NON-GRASS GROUND COVER PLANTING

THE TOPSOIL SPECIFICATIONS PROVIDE ENOUGH ORGANIC MATERIAL TO ADEQUATELY SUPPLY NUTRIENTS FROM NATURAL CYCLING. THE PRIMARY FUNCTION OF THE BIORETENTION STRUCTURE IS TO IMPROVE WATER QUALITY. ADDING FERTILIZERS DEFEATS, OR AT A MINIMUM, IMPEDES THIS GOAL. ONLY ADD FERTILIZER IF WOOD CHIPS OR MULCH ARE USED TO AMEND THE SOIL. ROTOTILL AREA FERTILIZER AT A RATE OF 2 POUNDS PER 1000 SQUARE FEET.

6. UNDERDRAINS

UNDERDRAINS SHOULD MEET THE FOLLOWING CRITERIA:

- PIPE- SHOULD BE 4" TO 6" DIAMETER, SLOTTED OR PERFORATED RIGID PLASTIC PIPE (ASTMF 758, TYPE PS 28, OR AASHTO-M-278) IN A GRAVEL LAYER. THE PREFERRED MATERIAL IS SLOTTED, 4" RIGID PIPE
- (E.G., PVC OR HDPE) • PERFORATIONS- IF PERFORATED PIPE IS USED, PERFORATIONS SHOULD BE 3/8" DIAMETER LOCATED 6"
- ON CENTER WITH A MINIMUM OF FOUR HOLES PER ROW. PIPE SHALL BE WRAPPED WITH A 1/2" (NO. 4 OR 4X4) GALVANIZED HARDWARE CLOTH. • GRAVEL- THE GRAVEL LAYER (NO. 57 STONE PREFERRED) SHALL BE AT LEAST 3" THICK ABOVE AND
- BELOW THE UNDERDRAIN • THE MAIN COLLECTOR PIPE SHALL BE AT A MINIMUM 0.5% SLOPE.

CONSIDERED PART OF THE FILTER BED WHEN BED THICKNESS EXCEEDS 24"

 A RIGID, NON-PERFORATED OBSERVATION WELL MUST BE PROVIDED (ONE PER EVERY 1,000 SQUARE FEET) TO PROVIDE A CLEAN-OUT PORT AND MONITOR PERFORMANCE OF THE FILTER. • A 4" LAYER OF PEA GRAVEL (1/8" TO 3/8" STONE) SHALL BE LOCATED BETWEEN THE FILTER MEDIA AND UNDERDRAIN TO PREVENT MIGRATION OF FINES INTO THE UNDERDRAIN. THIS LAYER MAY BE

THE MAIN COLLECTOR PIPE FOR UNDERDRAIN SYSTEMS SHALL BE CONSTRUCTED AT A MINIMUM SLOPE OF 0.5%. OBSERVATION WELLS AND/OR CLEAN-OUT PIPES MUST BE PROVIDED (ONE MINIMUM PER EVERY 100) SQUARE FEET OF SURFACE AREA)

7. MISCELLANEOUS

THESE PRACTICES MAY NOT BE CONSTRUCTED UNTIL ALL CONTRIBUTING DRAINAGE AREA HAS BEEN

I HEREBY CERTIFY THAT THE STORMWATER MANAGEMENT FACILITIES (BOTH BMPS AND ESD PRACTICES) SHOWN ON THE PLANS HAVE BEEN CONSTRUCTED IN ACCORDANCE WITH THE PLANS APPROVED BY THE CALVERT COUNTY DEPARTMENT OF PUBLIC WORKS., EXCEPT AS

> RED COLOR INDICATES ORIGINAL

> > C 4.1

THIS STAMP IN

FILE #: B - 57 - 3 D.2


282

2018



NOTED IN RED ON THE "AS-BUILT" DRAWINGS.

JOSEPH J. KADJESKI MD PE #31181



| | |
|------|--|
| # | SITE KEY NOTES |
| 1 | PROPOSED CONCRETE SIDEWALK TO MEET (FLUSH) WITH EXISTING ASPHALT OR CONCRETE EXISTING PAVEMENT TO BE SAW CUT TO PROVIDE CLEAN CONSTRUCTION JOINT |
| 2 | PROPOSED RELOCATED BUILDING LIGHT LOCATIONS. |


| PROPOSED PA | AVING LEGEND | | SITE & LAYOUT PLAN | IE GARDENS ~ SPR 2018 - 2 LDFLOWER MEADOW & PATIO D 11 PARCEL 389 ~ 13480 DOWELL F T DISTRICT, CALVERT COUNTY DOWELL, MARYLAND 20629 DR: KOENIG PRIVATE FOUNDATION |
|---------------------------------|--------------|-----|--------------------|--|
| DESCRIPTION | PROPOSED | 1 1 | | AIE (VILDFI VILDFI VILD |
| CONCRETE SIDEWALK | 4 4 4 | 1 | | MLD WILD GRID FIRST DC |
| HEAVY DUTY CONCRETE SIDEWALK | 4 4 4 |] | 7 | ANNMARIE WILD TM 44 GRID ' FIRST I DC |
| GRAVEL PATH | |] | PLAN | Z ≥ |
| ASPHALT SIDEWALK | |] | ITE P | |
| GRAP | HIC SCALE | | S | |

(IN FEET)
1 inch = 20 ft.

THIS STAMP IN
RED COLOR
INDICATES ORIGINAL
C 5.0

FILE #: B - 57 - 3 E

282



April 2018

www.ACODrain.us

Toll Free: (888) 490-9552

Fax: (520) 421-9899

© April 2018, ACO, Inc. This information is believed to be accurate but it is not gu

Toll free: (800) 543-4764

ax: (440) 639-7235

April 2018

Toll free: (800) 543-4764 Fax: (803) 802-1063

delete as appropriate

www.ACODrain.us

THIS STAMP IN RED COLOR INDICATES ORIGINAL C 6.0

 ∞

 ∞

20

SARDE OWER

NNMARIE (

14.000 PS

4211 Pleasant Ro

(3) VARIABLE SUMP DEPTH

(6" MIN. ON 8" - 24", 10" MIN. ON 30"

BUFORD, GA 3051

Nyloplast

Fort Mill, SC 29708 Tel: 440-639-7230 Fax: 803-802-1063

4,000 PSI 1,500 PSI

VEYOR LAND

FILE #: B - 57 - 3 F

IS DIRECTED TO AN APPROVED SEDIMENT CONTROL PRACTICE.

U.S. DEPARTMENT OF AGRICULTURE

JRAL RESOURCES CONSERVATION SERVICE

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

MARYLAND DEPARTMENT OF ENVIRONMENT


WATER MANAGEMENT ADMINISTRATION


Type KS2-902S

Type KS2-902S

Type KS2-902S Type KS2-902S

April 2018





X:\1-12800 Series\1-12812 Koenig\05-Drawing Files\C-site NEW

FILE #: B - 57 - 3 F.1